


IMPERIAL
FLOORING AUSTRALIA



PRODUCT BROCHURE



FLOORING ONLINE | IN-STORE

Imperial Flooring Australia: Premium Timber Flooring Solutions

Imperial Flooring Australia is an Australian family-owned business specialising in premium timber flooring for residential and commercial spaces.

With the showroom located in Unanderra and distribution centres in Wollongong, Sydney & Melbourne, we offer a range of hi-quality flooring options for nationwide shipping.

Our commitment to quality and customer service has made Imperial Flooring Australia a trusted partner for leading construction companies in Australia.

Services and Commitment

Imperial Flooring Australia is dedicated to providing high-quality flooring products and services to residential and commercial clients across Australia.

With a commitment to customer satisfaction and budget-friendly options, Imperial Flooring Australia is a one-stop shop for In-store or online products.

Our mission is to provide tailored flooring solutions to meet all needs and preferences. Home owners, designers or tradies can begin planning projects by ordering flooring samples online at any time or anywhere. Its really that simple!

Transform your space today!

Visit the Wollongong showroom or shop flooring online for convenient Australia-wide shipping.



We Ship Australia Wide!



**Australasian
Timber Flooring
Association**

PRODUCT RANGE

Offering our clients a complete flooring package solution ✓



Engineered Timber Flooring
Pages 4 - 14



Herringbone
Pages 7 + 8 + 11



Chevron
Pages 12 - 13



Hybrid Waterproof Flooring
Pages 15 - 18



Laminate Flooring
Pages 19 - 20



Foam & Acoustic Underlay
Pages 21



Flooring Adhesives
Pages 22



Floor Levelling Compounds
Page 23



Flooring Accessories & Tools
Pages 24 - 28

+ MUCH MORE

Chat to our team for your next flooring project solutions!



14mm Oak

COLOUR SPECIES SELECTION

Introducing the stunning 14mm Engineered Oak Timber Flooring, available exclusively at Imperial Flooring Australia. Crafted with a real timber top layer and multi-layer plywood inner structure core, this flooring adds a touch of luxury to any residential or commercial interior space. With each timber panel featuring unique characteristics and no repetitive patterns, this flooring collection offers a wide range of pre-finished colours, from light modern oak to darker oak tones. Upgrade your space with the beauty of Imperial Flooring Australia's Engineered Oak Timber Flooring.


Engineered timber flooring is not just a flooring option; it's a lifestyle statement. Imperial Flooring Australia's commitment to quality, innovation, and customer satisfaction makes them the perfect choice for transforming your space into a haven of luxury and style. Embrace the beauty of engineered timber flooring and let your floors tell a story of elegance and sophistication.

SPECIFICATIONS:


Timber Grade: Natural - ABCD
Dimension(mm): L1900 x W190
Thickness(mm): 14
Top Layer(mm): 2
Surface Finish: Brushed UV Lacquer
Gloss Level: 5-8% Super Matt
Nesting: Less than 25% random short boards
Edging: 4 Sided Micro-Bevel
Joining System: Tongue and Groove
Pack Size: 6 Planks / 2.166 m²
Weight: 26kg / per box
Slip Resistance: P3
Installation Methods: Floating on Underlay or Direct Glue Down
Warranty:

- Residential: 20 Years
- Commercial: By Request


Warranty Structural: Lifetime




NATURAL OAK




TUSCAN OAK



WHITE HAVEN




CREAM WHITE




COUNTRY OAK



LIGHT BROWN



PALE OAK



CEDAR BROWN



BLACK OPAL



SQUARE OVERHANG



FLUSH 90 DEGREE



BRASS INLAY



15mm Oak

COLOUR SPECIES SELECTION

Introducing our premium 15mm Engineered Oak Timber Flooring, exclusively available at Imperial Flooring Australia. Ideal for both residential and commercial spaces, this is manufactured with a real timber top layer and a multi-layer plywood inner structure core, providing a touch of luxury to any interior. Each timber panel boasts unique features, with no repetitive pattern to be found. Our 15mm Engineered Oak can be resurfaced during its lifespan, and is available in a wide range of pre-finished colours, from light modern oak to darker oak tones.

Engineered timber flooring is not just a flooring option; it's a lifestyle statement. Imperial Flooring Australia's commitment to quality, innovation, and customer satisfaction makes them the perfect choice for transforming your space into a haven of luxury and style. Embrace the beauty of engineered timber flooring and let your floors tell a story of elegance and sophistication.

SPECIFICATIONS:

Timber Grade: Natural - ABCD

Dimension(mm): L1900 x W190

Thickness(mm): 15

Top Layer(mm): 3

Surface Finish: Light Brushed Lacquer

Gloss Level: 5-8% Super Matt

Nesting: Less than 15% random short boards

Edging: 4 Sided Micro-Bevel

Joining System: Tongue and Groove

Pack Size: 5 Planks / 1.805 m²

Weight: 20kg / per box

Slip Resistance: P3

Installation Methods: Floating on Underlay or Direct Glue Down

Warranty:

- Residential: 20 Years
- Commercial: By Request


Warranty Structural: Lifetime



LIGHT NATURAL




WHITE WASH



NEUTRAL OAK



RAW OAK



TINGE OAK



GOLDEN OAK



SANDY BAY



HICKORY BROWN



CHARCOAL



20mm Oak

Explore the beauty of 20mm Engineered Oak Timber flooring exclusively at Imperial Flooring Australia. Perfect for residential & commercial spaces Manufactured with a real timber top layer (veneer) with a multi layer plywood inner structure core providing a touch of luxury to all residential & commercial interior spaces. Each timber panel provides unique features with no repetitive pattern to feature throughout the floor space. Our 20mm Engineered Oak can be resurfaced in its lifespan. All our Engineered Oak Timber Flooring collections are manufactured pre-finished (coated) ready to be installed, with a wide range of colours available, from light modern oak to darker oak tones.

SPECIFICATIONS:

Timber Grade: Natural - ABCD

Dimension(mm): L2200 x W220

Thickness(mm): 20

Top Layer(mm): 6

Surface Finish: Light Brushed UV Lacquer

Nesting: Less than 25% Random Short Boards

Gloss Level: 5-8% Super Matt

Edging: 4 Sided Micro-Bevel

Joining System: Tongue and Groove

Pack Size: 4 x Planks / 1.936m²

Weight: 27kg / per box

Slip Resistance: P3

Installation Methods: Direct Glue Down / Floating Floor

Warranty:

- Residential: 20 Years

- Commercial: By Request

Warranty Structural: Lifetime

COLOUR SPECIES SELECTION



HICKORY BROWN



RAW OAK



MINK GREY



LIGHT NATURAL



WHITE WASH



GOLDEN OAK



SANDY BAY



15mm Herringbone

Discover the timeless elegance of our 15mm Herringbone Parquetry Engineered Oak Timber flooring exclusively at Imperial Flooring Australia. Perfect for residential & commercial spaces. Manufactured with a real timber top layer (veneer) with a multi layer plywood inner structure core providing a touch of luxury to all residential & commercial interior spaces. Each timber panel provides unique features with no repetitive pattern to feature throughout the floor space. Our 15mm Engineered Oak can be resurfaced in its lifespan. All our Engineered Oak Timber Flooring collections are manufactured pre-finished (coated) ready to be installed, with a wide range of colours available, from light modern oak to darker oak tones.

Herringbone flooring is not just a flooring option; it's a lifestyle statement. Imperial Flooring Australia's commitment to quality, innovation, and customer satisfaction makes them the perfect choice for transforming your space into a haven of luxury and style. Embrace the beauty of engineered timber flooring and let your floors tell a story of elegance and sophistication.

SPECIFICATIONS:

- Timber Grade:** ABC
- Dimension(mm):** L600 x W120
- Thickness(mm):** 15
- Top Layer(mm):** 3
- Surface Finish:** Light Brushed UV Lacquer
- Gloss Level:** 5-8% Super Matt
- Edging:** 4 Sided Micro-Bevel
- Joining System:** Tongue and Groove
- Pack Size:** 16 Planks / 1.152 m²
- Weight:** 11kg / per box
- Slip Resistance:** P3
- Installation Methods:** Direct Glue Down Only
- Warranty:**
 - Residential: 20 Years
 - Commercial: By Request
- Warranty Structural:** Lifetime

COLOUR SPECIES SELECTION



RAW OAK



LIGHT NATURAL



MINK GREY



SANDY BAY



GOLDEN OAK



WHITE WASH




NEUTRAL OAK



HICKORY BROWN



TINGE OAK



CHARCOAL



15mm AB GRADE

Introducing our premium AB Grade 15mm Engineered Oak Timber Flooring, exclusively available at Imperial Flooring Australia. Ideal for both residential and commercial spaces, this is manufactured with a real timber top layer and a multi-layer plywood inner structure core, providing a touch of luxury to any interior. Each timber panel boasts unique features, with no repetitive pattern to be found. Our AB Grade 15mm Engineered Oak can be resurfaced during its lifespan, and is available in plank + herringbone + chevron.

This is the highest grade available in timber flooring. This wood is cut from the centre of the tree, and the wood from the centre is much more uniform and has far less knots & imperfections. AB grade flooring has a much lower sap content, usually no more than 5% of the board which leads to a more uniform colour across different boards. If you like an engineered timber floor with minimal feature and character this is for you.

SPECIFICATIONS:

Timber Grade: AB Grade

Dimension(mm): Length x Width

- **Plank:** 1900mm x 190mm
- **Herringbone:** 600mm x 120mm
- **Chevron:** 770mm x 125mm

Thickness(mm): 15

Top Layer(mm): 3

Surface Finish: Light Brushed Lacquer

Gloss Level: 5-8% Super Matt

Nesting: Less than 15% random short boards

Edging: 4 Sided Micro-Bevel

Joining System: Tongue and Groove

Pack Size:

- **Plank:** 6 Planks / 1.805 m²
- **Herringbone:** 16 Planks / 1.152 m²
- **Chevron:** 8 Planks / 1.54 m²

Slip Resistance: P3

Installation Methods: Floating on Underlay or Direct Glue Down

Warranty:

- *Residential:* 20 Years
- *Commercial:* By Request

PLANK COLOURS




BARLEY OAK




WHISPER OAK



BLONDE OAK



ASHOAK



TUDOR OAK

HERRINGBONE + CHEVRON COLOURS

Coming
Soon



AUSTRALIAN HARDWOOD

COLOUR SPECIES SELECTION

AUSTRALIAN PREMIUM NATIVE COLLECTION

AUSTRALIAN ENGINEERED TIMBER FLOORING

Introducing our unique Fiddleback Engineered Australian Hardwood collection. It's available in the ever popular Spotted Gum and Blackbutt. Fiddleback wear layers combine the classic features of our Australian Eucalyptus bonded onto an ever reliable Plywood core. This creates an authentic Australian timber visual with the associated stability and durability of an engineered timber construction

Variety Of Sizes

Surface finishes include smooth or brushed textures. Pre-finished matte, water based multi-coat PU lacquer. All sizes display Micro-bevel 4 sides to enhance the plank visual. The Fiddleback plank sizes are recommended as a floating installation and Direct Fix only for parquetry.

Key Features

- Extremely stable with excellent wear resistance
- Spotted Gum Janka 11kN
- Impact resistant, durable and stable
- Blackbutt Janka 9.1 kN

Profile

- Patented Click format for floating installation & direct stick.
- T&G for Herringbone & Rustic. Micro Bevelled edges, 4 sides.

Coating & Surface - Direct Stick Installations


- Smooth & light wire brushed, PU lacquer matte, approx. 10-15% gloss level in both brushed and smooth surface.



Herringbone
SPOTTED GUM




Herringbone
BLACKBUTT




Available in
Rustic Grade

125mm
SPOTTED GUM



Available in
Rustic Grade

125mm
BLACKBUTT



Available in
Rustic Grade

180mm / 189mm
SPOTTED GUM



Available in
Rustic Grade

180mm / 189mm
BLACKBUTT



9mm Hybrid

COLOUR SHADE SELECTION

SPECIFICATIONS:

- Type:** Hybrid Floating Flooring
- Thickness:** 9mm
(2mm Built in Acoustic 6 star Underlay)
- Width:** 228mm
- Length:** 1800mm
- Surface Finish:** UV Coating- Anti bacterial - Scratch Armor
- Edging:** Square Edge
- Profile:** Patented 5G Click System
- Waterproof:** 100%
- Installation Method:** Floating Floor
- Pack Size:** 1.6416m²
- Weight:** 24kg / per box
- Boards per pack:** 4 Boards
- Slip Resistance:** P4
- Wear Layer:** 0.5mm
- Construction:** PVC Embossed Wear Layer with Limestone & PVC Composite Core
- VOC Rating:** E1
- Warranty:** 20 years Residential + Commercial on request
- Structural Warranty:** Lifetime
- Accessories:** Matching Stair Nosing + Matching Scotia + L Angles + Reducers + T-Mouldings



LIGHT OAK



BONDI SANDS



NEW ENGLAND BLACKBUTT



SPOTTED GUM




BEACH OAK



LIGHT BEIGE




WHITE BAY



WARM BROWN



ASH GREY



SHADOW GREY



STAIN GUARD



EASY TO CLEAN



DURABLE



SCRATCH SAFE





8mm Hybrid

COLOUR SHADE SELECTION

SPECIFICATIONS:


- Type:** Hybrid Floating Flooring
- Thickness:** 8mm
(2mm Built in Acoustic 5 star Underlay)
- Width:** 230mm
- Length:** 1500mm
- Surface Finish:** UV Coating- Anti bacterial - Scratch Armor
- Edging:** Square Edge
- Profile:** 2G Click System
- Waterproof:** 100%
- Installation Method:** Floating Floor
- Pack Size:** 1.725m²
- Weight:** 22kg / per box
- Boards per pack:** 5 Boards
- Slip Resistance:** P4
- Wear Layer:** 0.5mm
- Construction:** PVC Embossed Wear Layer with Limestone & PVC Composite Core
- VOC Rating:** E1
- Warranty:** 20 years Residential + Commercial on request
- Structural Warranty:** Lifetime
- Accessories:** Matching Stair Nosing + Matching Scotia + L Angles + Reducers + T-Mouldings



BLONDE ASH



BLACKBUTT



FAWN



URBAN OAK



BRUSHED SPOTTED GUM



GREY IRONBARK



BRUSH GREY



WHITE OAK



STAIN GUARD



EASY TO CLEAN



DURABLE



SCRATCH SAFE



6.5mm Hybrid

SPECIFICATIONS:

Type: Hybrid Floating Flooring

Thickness: 6.5mm

(1.5mm Built in Acoustic 6 star Underlay)

Width: 182mm

Length: 1540mm

Surface Finish: UV Coating- Matt Embossed Surface

Edging: Square Edge

Profile: Licenced Click System

Waterproof: 100%

Installation Method: Floating Floor

Pack Size: 2.243m²

Weight: 23.5kg / per box

Boards per pack: 8 Boards

Slip Resistance: P3

Wear Layer: 0.5mm

Construction: Rigid Core; LVT balance layer; Cushion pad

VOC Rating: E0

Warranty: 20 years Residential + Commercial on request

Structural Warranty: Lifetime

Accessories: Matching Stair Nosing + Matching Scotia + L Angles + Reducers + T-Mouldings



STAIN
GUARD



EASY TO
CLEAN



DURABLE




SCRATCH
SAFE

COLOUR SHADE SELECTION



QLD SPOTTED GUM




PALOMA NATURAL



COTTON WHITE



STONE GREY




PALE TAN



COASTAL BLACKBUTT




BLACKBUTT



SNOWY WHITE



HARBOR GREY



NSW SPOTTED GUM



12mm Laminate

COLOUR SHADE SELECTION

Exclusive collection to Imperial Flooring Australia, commercial wear layer grade with 48hr water resistance protection. The perfect range for heavy traffic commercial & residential projects

Water Resistant

48 hours water protection resistant flooring.

Anti-Scratch Surface

Excellent resistant to scratches, scrapes and dents.

Authentic Colours

The feel and look of real wood flooring colour selections.

Easy Install & Maintenance

Easy DIY installation with the 2G Valinge clip system.

Pet Friendly

Perfect for pet owners whose pets frequently come back with muddy paws from a morning walk.

SPECIFICATIONS:

- Type:** Imperial Laminate Flooring
- Dimension(mm):** 1516mm (L) x 238mm (W)
- Thickness(mm):** 12mm
- Wear Rating:** AC4
- Core:** Water Resistant Treated Core
- Gloss Level:** Matte
- Joining System:** Valinge 2G Click System
- Pack Size:** 6 Planks / 2.1648 m²
- Installation Methods:** Floating Floor
- Warranty**
- Residential:** 20 Years
- Commercial:** On request
- Accessories:** Pre-Fabrication Matching Stair Nosing's & finishing trims



STRAW OAK



SCENIC OAK



OXFORD OAK



AUBURN BLACKBUTT



SOUTHERN SPOTTED GUM



IRONBARK



HARBOR GREY



AUBER OAK



12mm Laminate

COLOUR SHADE SELECTION


*Timber Feel & Look Laminate Flooring
Oakleaf HD plus collection*

SPECIFICATIONS:

- Type:** Timber Look Laminate Flooring
- Dimension(mm):** L2200mm x W196mm
- Thickness(mm):** 12mm
- Surface Finish:** High Definition Digital Print realistic timber visuals, colours, and textures.
- Gloss Level:** Super Matte
- Edging:** 4 Sided Micro-Bevel
- Joining System:** 5G Valinge Licenced Clip System
- Pack Size:** 4 Planks / 1.725 m²
- Patterns:** 30 different pattern designs
- Scratch / Wear Rating:** AC4
- Slip Test Rating:** P3
- Installation Methods:** Floating on Underlay
- Water Resistant:** 48 hours
- VOC:** E1
- Warranty Residential:** 20 Years
- Warranty Structural:** 25 Years
- Accessories:** Pre-Fabricated Stair Nosing's, Colour Matching 12mm C Channels & Finishing Trims



ALPINE MIST



AGED NATURAL




ARCTIC FOX



SIERRA OAK



BLACKBUTT



DELTA SAND



HICKORY




NATURAL



SILK GREY




WOLF GREY



SPOTTED GUM



CLOVE



BEDROCK



3mm Silver (2in1) Foam Underlay

SPECIFICATIONS:

Type: Standard Silver Foam
 Moisture Barrier Overlap: Yes
 Roll Size: 20sqm Roll
 Thickness: 3mm
 Width: 1metre
 Peel & Stick Tape: Yes
 AAAC Star Rating: 4
 Suitable Floor Coverings: Laminate, Bamboo & Engineered Flooring
 Strata Certified: No
 Installation Method: Floating Floor ONLY
 Installation of Underlay: Loose lay installation ONLY



3mm Acoustic Rubber Matting Underlay

SPECIFICATIONS:

Product: Floating Floor Underlay or Direct Glue Down
 Type: Rubber
 Colour: Multicolour
 Surface: Granular Texture
 Grade: Commercial & Residential
 Density: 850 Kg/m³
 Acoustic Performance: 43dB
 AAAC Star Rating: 5
 Roll Size:
 • 3mm = 10 sqm
 Width = 1metre
 Thickness: 3mm
 Suitable Floor Coverings: Laminate & Engineered Flooring
 Strata Certified: Yes
 Acoustic Report: Yes
 Installation Method: Floating Floor or Direct Dual Bond Stick Down (Glue)
 Installation of Underlay: Loose lay installation or glue down.
 Ground Level Concrete: Install Builders Plastic or Moisture Barrier first



5mm Acoustic Rubber Underlay 12.5m² Regupol 5512 Sonus Core 5

SPECIFICATIONS:

Product: Floating Floor Underlay or Direct Glue Down
 Type: Rubber
 Colour: Multicolour
 Surface: Granular Texture
 Roll Size: 12m² (10lm x 1.25m) Rolls
 Thickness: 5mm
 Weight: 46kg per roll
 Suitable Floor Coverings: Laminate, Timber, Parquetry & Engineered Timber Flooring
 Strata Certification: Yes
 Install Method: Floating Floor & Direct Dual Bond Glue
 Installation of Underlay: Glue Down Only!



Bostik Ultraset HP MS Polymer Timber Flooring Adhesive 16kg

Bostik Ultraset HP is a one part solvent and isocyanate free MS polymer based elastomeric adhesive formulated to adhere most types of timber flooring systems.

- Meets requirements for EN 14293:2006 "Adhesives for bonding parquet to subfloor"
- Non-hazardous, solvent and isocyanate free formulation
- Very low VOC
- Non flammable
- No mixing; ready to use
- Easy to spread while maintaining stable peaks
- Will not re-emulsify when in contact with moisture
- Tested to ASTM C794 for peel adhesion to various species of Australian hardwood
- Remains flexible after full cure
- Excellent initial grab and final bond strength
- Excellent acoustic properties
- Suitable over radiant heating
- Australian made

Recommended Uses

Adhering parquet, solid strip softwood and hardwood flooring, engineered flooring and bamboo flooring to concrete subfloors.

Adhering recommended acoustic underlays as an intermediate layer between subfloor and flooring system.

Specifications:

Colour: Brown

Viscosity: Smooth paste; holds peaks

Composition: MS Polymer

Application temperature: 5 to 30°C

Pack Sizes:

- 16kg Pail (10L)
- 600mL Sausage

Specific Gravity: 1.6 Approx.

Cure Rate: 2.5mm / 24hrs

Cure System: Moisture Cure

Full Cure: (1mm film) Approx. 18-24hrs Depending on temperature and relative humidity. Curing time extended in low humidity

Elongation: 300%

Walk on time: 16hrs - light traffic

Tack Free time: Approx. 1.25hrs @ 23°C 50% RH

Shore A Hardness: Approx. 50

Tensile Strength in Shear (2mm) Timber to Timber - BS EN 14293
1.3N/mm

Coverage: V3 Notch = 1.2-1.4m² / per litre V4 Notch = 1-1.2m² / per litre

Suitable For:

- Solid Timber
- Engineered Timber
- Parquetry
- Timber Stair Installs
- Hybrid & Laminate Stair Installs
- Plywood
- Rubber Underlay Matting
- Installing Trims



Bostik Ultraset 3in1 Acoustic Timber Flooring Adhesive 26kg

Bostik Ultraset 3 in 1 is a high performance flooring adhesive, moisture control, and sound reduction membrane all in one. Bostik's breakthrough AXIOS® Tri-Linking™ Polymer Technology is used in this formulation, maintaining the superior long term durability, moisture control and sound abatement properties of high end urethane adhesives.

- 3 in 1 adhesive, moisture control and sound reduction membrane
- Thickness Control™ Spacer Technology maintains thickness between hardwood flooring and substrate
- Extremely low moisture vapour permeability
- Superior sound control typically outperforms 3mm rubber underlay
- 3mm Anti-fracture performance can bridge cracks up to
- Zero VOC (as calculated per SCAQMD Rule 1168)
- No restriction on board width or length
- Blockade® anti-microbial protection

Recommended Uses:

Suitable substrates include: concrete, terrazzo, ceramic tiles, timber, plywood and cement backer board- Adheres parquet, cork, solid strip softwood, hardwood flooring, engineered flooring and bamboo flooring.

Coverage:

V4 Flat Notch (4.8mm) = 20-22m² @ 4.8mm Trowel Spread

V6 Notch Trowel (6mm) = 12-13m² @ 6mm Trowel Spread



WAKOL PU280 - Moisture Barrier - 1 Component Ready to use Full Membrane

Wakol PU 280 is a ready-to-use 1-component polyurethane primer for priming absorbent and non-absorbent subfloors, and to reinforce abraded resp. sanded concrete edges. Also for capillary ascending humidity and higher residual humidity up to 6 CM% / 98 corresponding RH % in cement screeds without floor heating, on heated cement screeds up to max. 3 CM% / 85 corresponding RH % as well as on concrete up to max. 7,5% by weight / 98 corresponding RH %; applicable as moisture barrier on unheated cement screeds and concretes without prior moisture measurement.

Suitable Applications:

Porous & NON-Porous Surfaces

- Concrete
- Screed
- Timber
- Plywood
- Tiles
- Most Surfaces

Coverage:

1 Coat @ 150µm wet film

- 5L Consumption = 45 m²
- 11L Consumption = 100-110 m²





DL55 Indoor Floor Self Levelling Compound 20kg

Description:

DL55 is an advanced cement and polymer based levelling and smoothing compound. DL55 is formulated for experienced commercial contractors to smooth and level large commercial and retail areas. Once dry it is suitable for the application of timber flooring, vinyl, carpet and tile floor finishes. Unlike normal hydration levellers, DL55 will harden and dry at temperatures down to 10°C.

Composition:

- Super smooth – requires no sanding
- Versatile – apply **1.5mm to 75mm** in one application
- Rapid hardening – walkable from 2 hours
- Superior flow – fast application
- Flexible – hand mix or pump application

Technical Data:

Compression Strength

After 1 Day Approx. 15MPa
 After 7 Days Approx. 25MPa
 After 28 Days Approx. 35MPa

Tensile Bending Strength

After 1 Day Approx. 5MPa
 After 7 Days Approx. 7MPa
 After 28 Days Approx. 10MPa

Colour: Grey

Water / Compound Ratio: 4.4L / 20kg bag

Working Time: 20-30 minutes

Pack-size: 20kg/bag

Coverage: Covers approx. 5m² at 3mm thick



DP70 Universal Porous & Non Porous Primer 5kg + 20kg Drums

Description:

Cemimax DP70 is a low emission, multi-purpose dispersion primer for for existing surfaces on **indoor & outdoor** applications. Use on surfaces with well-bonded, waterproof adhesive and smoothing compound residues.

Technical Data:

Packaging: Plastic bucket

Pack size:

- 5kg / 4L
- 20kg / 16L

Shelf-life: 12 months

Touch Dry Time: 15 -20min

Coverage: Approx. 12m² /1 Litre

Drying time: 4-6 hours

Suitable for CONCRETE, TIMBER, TILES, PLYWOOD, SLATE + more



DL59 Indoor + Outdoor Floor Premium Self Levelling & Overlayment Compound 20kg

Description:

DL59 is a cement based leveling compound with very high compressive strength to C40. DL59 is especially suitable for high traffic and heavy wear locations. DL59 can be also used as overlays for polished concrete. Suitable for all floor coverings

Composition:

- Super smooth – requires no sanding
- Extremely high strength of compression and bending
- Versatile – apply **1.5mm to 40mm** in one application
- Rapid hardening – walkable from 2 hours
- Superior flow – fast application
- Flexible – hand mix or pump application
- Can be polished
- Can add colours & aggregate to mix

Technical Data:

Compression Strength

After 1 day approx. 15MPa
 After 7 days approx. 25MPa
 After 28 days approx. 40MPa

Tensile Bending Strength

After 1 day approx. 5MPa
 After 7 days approx. 7MPa
 After 28 days approx. 10MPa

Colour: Grey

Water / Compound Ratio: 4.0L / 20kg Bag

Working Time: 20-30 minutes

Pack-size: 20kg/bag

Coverage: Covers approx. 5m² at 3mm thick



TILES



CONCRETE



TIMBER



OUTDOORS



WET AREAS



THOR FLOOR PROTECTION MATTING ROLLS

40metres x 750mm (30m² Rolls)



form-A-guard is a triple layered, foam backed, nonabrasive surface protection product, which is suitable for protecting solid floors including polished timber, parquetry, vinyl, tiles, slate, marble and polished concrete (sealed only). The form-A-guard is also suitable for the protection of kitchen and bathroom sinks, bench tops, vanity basins, bath tubs and shower bases.

Also recommended for use with the form-A-guard, is the THOR Membrane Tape and Joining Tape. The THOR Membrane Tape is a low tack, clean release tape that can be applied directly to the perimeter of a cleaned surface area. It is advised that periodic checks should be conducted on the THOR Membrane Tape after 1 month of application to ensure clean removal.

DIMENSIONS:

Size: 750mm wide x 40m long , covers 30sqm



THOR JOINING TAPE

THOR printed Joining Tape has been specifically designed to safely join form-A-guard to secure and prevent movement whilst protecting your valuable surfaces. THOR Joining Tape offers a strong bond and as such should not be applied directly to any finished or polished surface.

**** THOR Joining Tape is not to be applied directly to any finished surface ****

DIMENSIONS:

Size: 48mm wide x 100metre long tape roll



THOR EDGE TAPE PRE-APPLICATION

THOR Pre-App PVC tape has been specifically designed for cured, sealed and finished solid surfaces such as walls, tiles, bench tops, engineered timber flooring etc. The Pre-App tape can also be used as a perimeter or a membrane tape.

FEATURES:

- Easy release
- Clean removal
- UV stabilised

DIMENSIONS:

Size: 48mm wide x 66metre long tape roll



ONE STOP SHOP FLOORING STORE



WHITE NON - MARKING
MALLETS



TROWELS V3 + V4 + V6
TIMBER FLOORING



SAUSAGE GUNS 600ML



CLEANING WIPES
NON-SCRATCH



PRO CUTTING
TOOLS



BOSTIK ADHESIVES
& ACCESSORIES



FLOOR LEVELING
COMPOUNDS & PRIMERS



UNDERLAY



GAUGE RAKE FLOOR
LEVELLING



STAND UP FLOOR
LEVELING TROWELS



SPIKE ROLLER
FLOOR LEVELLING



DIY FLOOR
LAYING KIT



PULLING IRON



WAKOL MS335 REPAIR
HOLLOW SPOTS



SCRATCH REPAIR



GEL KNEE PADS
FOR FLOOR LAYING

SHOP ONLINE: www.imperialflooringaustralia.com.au/shop



PRE-FABRICATED STAIR NOSINGS **SQUARE EDGE WITH OVERHANG** ENGINEERED TIMBER FLOORING



PRE-FABRICATED STAIR NOSINGS **FLUSH BOX** ENGINEERED TIMBER FLOORING



PRE-FABRICATED STAIR NOSINGS MATCHING COLOUR TO **HYBRID** FLOORING OPTIONS



PRE-FABRICATED STAIR NOSINGS MATCHING COLOUR TO **LAMINATE** FLOORING OPTIONS



CHAMPAGNE - C CHANNEL END TRIM - ALL SIZES



SILVER - C CHANNEL END TRIM - ALL SIZES



BLACK - C CHANNEL END TRIM - ALL SIZES



COLOUR MATCHING - C CHANNEL END TRIM ENGINEERED TIMBER



COLOUR MATCHING L ANGLES - LAMINATE & ENGINEERED



COLOUR MATCHING L ANGLES - HYBRID



COLOUR MATCHING C CHANNELS - HYBRID



COLOUR MATCHING C CHANNELS - LAMINATE

PERIMETER EXPANSION GAP SCOTIA BEADINGS FIXED TO EXISTING OR NEW SKIRTING BOARDS



WHITE
SCOTIA



NATURAL OAK
SCOTIA



LIGHT OAK
SCOTIA



BROWN
SCOTIA



GREY
SCOTIA



NEW ENGLAND BLACKBUTT
SCOTIA



SANDSTONE
SCOTIA



SPOTTED GUM
SCOTIA



BLACK
SCOTIA









Sales Inquiries

Contact: 1300 676 176

Email: info@imperialflooringaustralia.com.au

HEAD OFFICE + SHOWROOM

2/25 Investigator Drive
Unanderra NSW 2526

Wollongong | Sydney | Melbourne

DISTRIBUTION CENTRES

atfa | Australasian
Timber Flooring
Association

IMPERIAL

FLOORING AUSTRALIA

WHOLESALE - COMMERCIAL - TRADE - RETAIL - DIY

FLOORING PACKAGES

www.imperialflooringaustralia.com.au